

TITLE OF THE INVENTION

IMAGE DATA ACQUISITION METHOD

CROSS-REFERENCE TO RELATED APPLICATION

This application is based upon and claims the
5 benefit of priority from the prior Japanese Patent
Application No. 2000-287618, filed September 21, 2000,
the entire contents of which are incorporated herein by
reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

The present invention relates to an image data
acquisition method for scanning a sample such as a DNA
(microarray (DNA chip), for example, by light beams in
a two-dimensional manner, and measuring reflection
15 light, transmission light, scattered light or
fluorescence from the sample, thereby acquiring scanned
image data.

2. Description of the Background Art

In recent years, there has been introduced a DNA
20 microarray technique as means for implementing a large
amount of gene expression and analysis within a short
time. In this DNA microarray, solution containing a
gene DNA is dropped by some nanoliters on a substrate
such as a slide glass, a stain-like spot of some tens
25 to 100 microns in diameter is formed, and these spots
are regularly arrayed in some thousands to some ten
thousands points on a substrate.

On such a DNA microarray, an RNA being a sample is distributed after labeled by fluorescence, and is washed, and fluorescence generated by emitting laser light to each spot is measured. A gene expression can
5 be analyzed by a fluorescence intensity.

A scanning type optical measuring device called a DNA microarray reader is used for measuring fluorescence during this gene expression and analysis. A configuration of this scanning type optical measuring
10 device is similar to that of a general confocal laser microscope. That is, the laser light emitted from a laser light source is irradiated onto a DNA microarray 3 through an objective lens. The fluorescence generated by irradiation of this laser light is guided
15 to a photoelectric conversion element such as photo multiplier tube (PMT) through a confocal pinhole. Then, a fluorescence intensity is converted into an electrical signal by this photoelectric conversion element.

20 At this time, the DNA microarray 3 is placed on an electrically driven scanning stage, and is moved in an XY direction. Therefore, the DNA microarray 3 is scanned by the laser light emitted from the laser light source in the XY direction, and the electrical signal
25 outputted from the photoelectric conversion element at this time is transmitted to an image processing device comprising a computer or the like. This image

processing device A/D converts the electrical signal from the photoelectric conversion element, and acquires scanned image data.

5 The scanned image data thus acquired is temporarily stored in a storage medium such as a hard disk as general-purpose image data such as Tagged Image File Format (TIFF) or Bit Map format after all of desired regions set before starting measurement have been scanned. Then, the temporarily stored data is
10 read out by dedicated analysis software, and desired data processing is done, whereby analysis data is obtained.

As a scanning type optical measuring device having its similar function, for example, a laser scanning
15 type cytometer is disclosed in Japanese Patent Application KOKAI Publication No. 8-114540. This laser scanning type cytometer scans cell groups that are interspersed in random on a slide glass by laser light. A signal light such as reflection light, transmission
20 light, scattered light or fluorescence from the cell group at this time is measured, and scanned image data is acquired. This statistic data indicating immunological characteristics and genetic characteristics of the cell group is computed from this
25 scanned image data.

A configuration of this laser scanning type cytometer is similar to a scanning type optical

measuring device called the above DNA microarray reader except that main scanning is optically carried out by utilizing a galvano mirror or the like.

On the other hand, a method of acquiring scanned
5 image data is executed as follows. Every time each
scanning image of a predetermined region size
(hereinafter, referred to as a strip) is acquired,
image processing relevant to such scanning image is
carried out, thereby recognizing cells acquired by each
10 strip. Then, analysis data such as area, fluorescence
intensity, and total fluorescence quantity for
individual cells are sequentially computed.

When scanning in all of the predetermined ranges
has been completed, statistic data is computed from
15 analysis data on all the acquired cells. Scanned image
data is used for calculating the above analysis data.
Therefore, the scanned image data is discarded
immediately when data analysis completes. In this
respect, a laser scanning type cytometer is different
20 from the above DNA microarray reader.

As a device for imaging a wide range of samples
such as a cell group on a slide glass, a method of
utilizing a laser scanning type microscope, for example,
is disclosed in Japanese Patent Application KOKAI
25 Publication No. 10-333056. A configuration of this
laser scanning type microscope is different from that
of the above DNA microarray reader in that

two-dimensional scanning is optically carried out by using a galvano mirror. In addition, the laser scanning type microscope is different from the laser scanning type cytometer in that sub-scanning can be
5 optically carried out, and a confocal optical system is provided.

A method of acquiring scanned image data is carried out as follows. When scanned image data in one field of view is acquired by optical two-dimensional
10 scanning, an electrically driven scanning stage is moved, and goes to the adjacent region. Further, scanned image data in one field of view at the object region is acquired by optical two-dimensional scanning. By repeating this, a plurality of partial scanned image
15 data are acquired relevant to a predetermined region. Then, respective partial scanned image data are strung, and scanned image data in all regions is acquired to be stored in a storage medium.

Of the above methods of acquiring scanned image
20 data, the DNA microarray reader carries out two-dimensional scanning by an electrically driven scanning stage, thus making it possible to scan a wide range. However, a scanning speed is slower by some tens times as compared with another optical scanning method. Thus,
25 a couple of minutes to some tens of minutes is required for scanning all of the regions of some tens of millimeters in square. Therefore, scanned image data cannot

be obtained from the start to the end of scanning, and thus, analysis data cannot be obtained in real time.

5 The laser scanning type cytometer acquires one item of scanned image data, and sequentially carries out image processing every time each strip is scanned. Therefore, the real time properties of analysis data that is problematic in DNA microarray reader can be solved. However, scanned image data is discarded when image processing is carried out, and analysis data is
10 computed. Therefore, the scanned image data on each strip or scanned image data on all the scanning regions cannot be acquired or stored.

There is provided a problem that the laser scanning type cytometer cannot carry out analysis
15 processing precisely when cells targeted for measurement exist across the boundary of strips, or alternatively, cannot recognize the cells. When the DNA microarray is measured by a similar method, the precision of a spot position differs depending on a
20 spot generating device, and thus, there is a possibility that a spot position at an end of one strip comes out of a scanning region.

In an example utilizing a scanning laser microscope, partial images are sequentially acquired,
25 and scanned image data in all the scanning regions is finally acquired. However, it is presumed that partial image data is shared with another task or program, and

thus, analysis processing cannot be carried out until final scanned image data in all the regions has been stored in a recording medium. Further, each item of the partial image data is fixed, and thus, there is a possibility that a measurement object is spanned at the boundary section of partial image data in the same way as when the laser scanning type cytometer is used. Therefore, when only partial image data is analyzed, precious result cannot be obtained.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to provide an image data acquisition method for analyzing a scanning time relevant to a sample and scanned image data from scanning relevant to the sample, thereby making it possible to minimize a time for computation of the analysis data.

The image data acquisition method according to the present invention is characterized by comprising: scanning a sample by a light; receiving a light from the sample, to acquire a scanned image data; and storing the scanned image data obtained by scanning a region of a predetermined size every time a region scanned by the light reaches a predetermined size, sequentially.

In the above image data acquisition method, preferable manners are as follows. The manners each may be applied independently, and may be applied in

combination as required.

5 (1) The size of the scanned region by the light is changed according to an arrangement position thereof when a plurality of measurement objects are arranged in the sample.

(2) In (2), position information on respective scanning regions is stored to be added to each item of the scanned image data sequentially stored.

10 (3) In (2), the sample is a DNA microarray in which a number of spots are arranged as a measurement object, and the size of the scanning region is such that a boundary in the scanning region is not overlapped on the spot.

15 (4) In (2), the scanning by the light is carried out by main scanning and sub-scanning in a direction orthogonal thereto, and adjustment of the size of the scanning region is carried out by regulating the number of scanning lines of the main scanning.

20 (5) An analysis processing is executed for the stored scanned image data in parallel with scanning of a next region when the storage of the scanned image data completes.

25 (6) In (5), the sample is a DNA microarray in which a number of spots are arranged as a measurement object, and the size of the scanning region is such that a boundary in the scanning region is not overlapped on the spot.

(7) The scanning by the light is carried out by main scanning and sub-scanning in a direction orthogonal thereto, and both of the main scanning and the sub-scanning are carried out by moving the sample.

5 (8) The scanning by the light is carried out by main scanning and sub-scanning in a direction orthogonal thereto, and the main scanning is carried out by an optical scanner.

10 Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

15 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

20 FIG. 1 is a view showing a configuration of a scanning type optical measuring device to which an image data acquisition method according to a first embodiment of the present invention is applied;

FIG. 2 is a diagram showing a configuration of a

data processing device in a scanning type optical measuring device to which the image data acquisition method according to the first embodiment of the present invention is applied;

5 FIG. 3 is a view showing laser light scanning and one strip on a DNA microarray in a scanning type optical measuring device to which the image data acquisition method according to the first embodiment of the present invention is applied;

10 FIG. 4 is an external view of a DNA microarray to be measured by an image data acquisition method according to a second embodiment of the present invention;

15 FIG. 5A and FIG. 5B are enlarged views when a spot line on the DNA microarray to be measured by the image data acquisition method according to the second embodiment of the present invention is spanned at a boundary section of strips;

20 FIG. 6A and FIG. 6B are enlarged views when a partial spot on the DNA microarray to be measured by the image data acquisition method according to the second embodiment of the present invention is spanned among a strip;

25 FIG. 7 is a graph illustrating data acquisition when a spot line is spanned at the boundary section of strips in the image data acquisition method according to the second embodiment of the present invention; and

FIG. 8 is a graph illustrating data acquisition when a partial spot is spanned at the boundary section of strips in the image data acquisition method according to the second embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, preferred embodiments of the present invention will be described with reference to the accompanying drawings.

FIG. 1 is a view showing a configuration of a scanning type optical measuring device to which an image data acquisition method according to the present invention is applied. A DNA microarray 3 shown in FIG. 3 that will be described later in detail, for example is placed on an electrically driven XY scanning stage 10.

A collimator lens 13 and an optical path division element 14 comprising a dichroic mirror are disposed on an optical path for laser light 12 outputted from a laser light source 11. The optical path division element 14 has a characteristic that reflects the laser light 12 outputted from the laser light source 11 and transmits fluorescence generated in the DNA microarray 3. An objective lens 16 is disposed on a reflection light path of the optical path division element 14 via a lens 5. A photoelectric conversion element 18 using a photoelectric multiplexing tube (PTM) is disposed on

a transmission optical path of the florescence from the DNA microarray 3 via a lens 17. The photoelectric conversion element 18 converts incident fluorescence into an electrical signal according to its light intensity, and transmits the converted electrical signal to a data processing device 19.

An optical scanner such as a galvano mirror is inserted on the optical path from the objective lens 16 to the optical path division element 14, whereby main scanning of the laser light 12 may be optically carried out instead of the electrically driven XY scanning stage 10. In addition, main scanning may be carried out by using a plurality of laser light sources and photoelectric conversion elements so as to correspond to a variety of label pigments.

FIG. 2 is a diagram showing a configuration of a data processing device 19. The data processing device 19 comprises a CPU 20, a system memory 21, a storage medium 22, an A/D conversion board 23, and a board for equipment control 24. The system memory 21 stores data acquisition software using an image data acquisition method according to the present invention. In addition, the system memory 21 forms a unshared memory for temporarily storing data captured and collected from the A/D conversion board 23 (digital electrical signal from the photoelectric conversion element 18).

The storage medium 22 comprises a hard disk or the

like for filing a digital electrical signal stored in the unshared memory in the system memory 21, and storing the filed signal as scanned image data.

5 The A/D conversion board 23 digitizes the electrical signal from the photoelectric conversion element 18.

The board for equipment control 24 outputs an XY scanning control signal to the electrically driven XY scanning stage 10.

10 The data processing device 19 can be connected to another computer 26 via a network 25. The computer 26 analyzes and processes the scanned image data stored in the storage medium 22. Use of the computer 26 reduces a burden of the CPU 20 in the data processing device 19.

15 The CPU 20 executes the data acquisition software stored in the system memory 21, and outputs the XY scanning control signal to the electrically driven XY scanning stage 10 through the board for equipment control 24. Then, laser light is scanned on the DNA
20 microarray. FIG. 3 is a view showing a DNA microarray and laser light scanning and one strip on the DNA microarray. As shown in FIG. 3, a stain-like spot 2 of about some tens to hundreds of microns in diameter formed by dropping or applying solution containing a
25 genetic DNA by some nanoliters is regularly arranged in some thousands to some ten thousands of points. Scanning of the laser light 12 is defined such that a Y

scanning direction is a main scanning and an X scanning direction is a sub-scanning in the specification.

The CPU 20 executes the data acquisition software stored in the system memory 21, receives fluorescence
5 from a plurality of the spots 2 when the laser light 12 is scanned on the DNA microarray 3, and acquires scanned image data. At this time, the CPU sequentially stores in the storage medium 22 the scanned image data obtained every time the scanning region of the laser
10 light 12 reaches a region of a predetermined size, for example, one strip, i.e., when scanning of each of the strips, i.e., first strip, second strip, and third strip completes.

Now, an operation of the device configured as
15 described above will be described here.

The laser light 12 outputted from the laser light source 11 is incident to the optical path division element 14 through the collimator lens 13, is reflected by the optical path division element 14, and is emitted
20 to the DNA microarray 3 via from the lens 15 to the objective lens 16.

At this time, the DNA microarray 3 is scanned by the laser light under the control of the CPU 20.

When the DNA microarray 3 is scanned by the laser
25 light 12, the fluorescence emitted from the DNA microarray 3 transmits from the objective lens 16 to the lens 15 and the optical path division element 14,

and is focused on the photoelectric conversion element 18 by the lens 17.

5 The photoelectric conversion element 18 converts the incident fluorescence into an electrical signal according to its light intensity, and outputs the converted signal to the data converting device 19.

 The CPU 20 starts scanning by the laser light 12 from a predetermined scanning start point S1. When the laser light reaches a point S2, one strip is completed.

10 The number "n" of scanning lines of the first strip from the scanning start point S1 to the point S2 is determined by the number "s" of capture lines of the spot 2 in one strip, a distance D between the respective spots 2, and a scanning interval "d", and is
15 assigned by the formula below.

$$n = s \cdot D/d \quad (1)$$

 For example, when spots 2 arranged at intervals of 200 microns are captured in 10 lines in one strip by scanning laser light 12 at intervals of 5 microns, the
20 number of scanning lines is 400.

 The CPU 20 temporarily stores data captured in the A/D conversion board 23 (electrical signal produced by digitizing an analog signal from the photoelectric conversion element 18) in the unshared memory in the
25 system memory 21. When the CPU 20 acquires data in number of scanning lines for the first strip shown in FIG. 3, the CPU files the digital electrical signal

stored in the unshared memory, and stores the filed signal as scanned image data in the storage medium 22.

Next, the CPU 20 starts scanning by the laser light 12 from a point S3, and temporarily stores the electrical signal from the photoelectric conversion element 18 in the unshared memory in the system memory 21 until the laser light has reached a point S4. Then, when the CPU 20 acquires data in number of scanning lines for the second strip shown in FIG. 3 after scanning of the laser light 12 has reaches the point S4, the CPU files the digital electrical signal stored in the unshared memory, and stores the filed signal in the storage medium 22 as new scanned image data.

Subsequently, each item of the scanned image data for each strip is stored in the storage medium 22. When scanning of the laser light 12 reaches a point S12, the CPU 20 completes scanning for all regions relevant to the DNA microarray 3.

On the other hand, the CPU 20 stores in the storage medium 22 each item of the scanned image data on each strip such as a first strip, a second strip, and a third strip, and executes analysis processing for these items of the scanned image data.

In this way, in the first embodiment, when fluorescence from a plurality of the spots 2 is received, and scanned image data is acquired when the laser light 12 is scanned on the DNA microarray 3,

every time the scanning region of the laser light 12 reaches one strip, items of scanned image data each obtained by scanning such one strip are sequentially stored in the storage medium 22. Therefore, a multi-
5 task compatible operation system is employed for the data processing device 19. Then, data acquisition software and image processing software are initiated, and every time new scanned image data is produced in a specified directory, the image processing software is
10 set so as to operate. In this manner, every time each item of the scanning data on each strip such as the first strip, second strip, and third strip is produced, analysis data can be sequentially obtained.

Therefore, a required time between scanning for
15 each spot 2 on the DNA microarray 3 and analysis of scanned image data from scanning for each of the spots 2, followed by computing the analysis data can be minimized.

A second embodiment of the present invention will
20 be described with reference to the accompanying drawings. A configuration of a scanning type optical measuring device to which the image data acquisition method according to the present invention is applied is identical that shown in FIG. 1 and FIG. 2. Here, a
25 description of the difference elements will be given below.

A CPU 20 executes data acquisition software stored

in a system memory 21, thereby changing a size of one strip for scanning laser light 12 according to an arrangement position of a plurality of spots 2 on a DNA microarray 3.

5 In addition, the CPU 20 executes the data acquisition software stored in the system memory 21, thereby adding scanning position information for items of scanned image data each sequentially stored in a storage medium 22.

10 In addition, the CPU 20 executes the data acquisition software stored in the system memory 21, thereby storing scanned image data and executing analysis processing for the scanned image data.

15 In the meantime, the DNA microarray 3 is produced by dropping solution containing a genetic DNA as described above on a substrate 1 such as a base processed slide glass. Thus, each spot 2 is not always formed in a true circle, and may extend off the line of the spot 2 significantly. In addition, a displacement
20 between a position of the spot 2 and a scanning start position may occur, and spot intervals may be not constant. In such a case, the spot 2 is spanned at the boundary of respective strips.

25 FIG. 4 is a an external view of a DNA microarray 3 in the above case. In FIG. 4, a boundary section between a first strip and a second strip is included in intervals for spot lines, and the spot 2 is included

without being spanned in the strip. However, at a boundary section between the second strip and a third strip, as shown in FIG. 5A, a stop line is spanned in the strip boundary section. Alternatively, at a
5 boundary section between the third strip and a fourth strip, as shown in FIG. 6A, a partial spot 2 is spanned between the strips.

In such a case, the CPU 20 executes the data acquisition software stored in the system memory 21,
10 thereby adjusting the number of scanning lines for the laser light 12 as required so that the spot 2 is not broken by the strip boundary section according to the arrangement position of a plurality of the spots 2 on the DNA microarray 3. Then, the CPU 20 changes the
15 size of one strip for scanning the laser light 12, i.e., acquires scanned image data in proper image size, and stores the acquired data in the storage medium 22. The CPU 20 continuously acquires the next scanned image data so as to be continuous with the acquired scanned
20 image data by immediately preceding scanning.

A specific processing operation will be described.
(a) In a case (FIG. 5A) where a spot line is spanned at a strip boundary section as in the boundary section between the second strip and the third strip (a portion
25 Q1 shown in FIG. 4)

The CPU 20 acquires the number of scanning lines set for one strip, and completes acquisition of data

for one strip. At this time, it is assumed that a last scanning line position L1 is set a substantial center of a spot line as shown in FIG. 5A. When a fluorescence intensity I on this last scanning line is obtained, a distribution f1 is obtained such that the luminescence is increased for each spot 2 as shown in FIG. 7. In FIG. 7, the fluorescence intensity I is defined on a vertical axis, and a main scanning direction (Y direction) is defined in a horizontal axis.

10 The CPU 20 returns the scanning line position L1 along a sub-scanning direction (X direction) as shown in FIG. 5B until thresholds in all the pixels have been lower than a predetermined threshold "Ith". Then, a last scanning line position L2 for one strip moves
15 between spot lines as shown in FIG. 5B, and the fluorescence intensity I is obtained as a distribution f2 as shown in FIG. 7.

 Here, the CPU 20 sets the last scanning line position to the scanning line position L2 after
20 movement, as shown in FIG. 5B. That is, the position L2 is recognized as a boundary section between the second strip and the third string. Then, scanned image data on the number of scanning lines fewer than a predetermined number of scanning lines is stored in the
25 storage medium 22.

 At this time, the CPU 20 adds to a header section of scanned image data the scanning position information

for each item of scanned image data, for example, the number of scanning lines in a second strip, a position coordinate when the second strip starts and ends, an integrated scanning line number from the first scanning line or the like, and stores the data in the storage medium 22.

(b) In a case (FIG. 6A) where a partial spot 2 is spanned between strips as in the boundary section between the third strip and the fourth strip (portion Q2 shown in FIG. 4)

The CPU 20 acquires the number of scanning lines set for one strip, and completes acquisition of data for one strip. At this time, it is assumed that the last scanning line position L1 is spanned at the boundary section between the third strip and the fourth strip as shown in FIG. 6A. When the fluorescence intensity I on the last scanning line is obtained, a distribution f3 is obtained such that the intensity at the portion of the spot 2 spanned between strips is increased as shown in FIG. 8.

The CPU 20 returns the scanning line position L1 along the sub-scanning direction (X direction) as shown in FIG. 6B until the thresholds in all the pixels have been lowered than a predetermined threshold "Ith". By doing so, the last scanning position L2 for one strip moves to a position at which the position does not pass through which the spot 2 spanned between the strips as

shown in FIG. 6B, and the fluorescence intensity I is obtained as a distribution f4 as shown in FIG. 8.

Here, the CPU 20 sets the last scanning position to the last scanning line position L2 after movement, as shown in FIG. 6B. That is, this position L2 is recognized as the boundary section between the third strip and the fourth strip. Then, scanned image data on the number of scanning lines fewer than a predetermined number of scanning lines is stored in the storage medium 22.

At this time, the CPU 20 adds to a header section of scanned image data the scanning position information for each item of scanned image data, for example, the number of scanning lines in a third strip, a position coordinate when the third strip starts and ends, an integrated scanning line number from the first scanning line or the like, and stores the data in the storage medium 22.

In this way, in the second embodiment, the size of each strip scanning the laser light 12 is changed according to the arrangement position of a plurality of the spots 2 on the DNA microarray 3. Therefore, in addition to an effect according to the first embodiment, even when the spot 2 is not always formed in a perfect circle, as the case may be, the spot significantly comes out of the line of the spots 2, or a displacement between a position of spot 2 and a scanning start

position occurs, or alternatively, spot intervals are not constant, and the spot 2 is spanned at the boundary between the strips, scanned image data can be stored without cutting the spot 2.

5 The CPU 20 adds the scanning position information to the scanned image data stored in the storage medium 22, thus making it possible to obtain an absolute position of each spot 2 on the DNA microarray 3.

10 Although the above described embodiments each have described the present invention by way of example when the image data acquisition method according to the present invention is applied to a DNA microarray reader, the present invention is applicable to a laser scanning type microscope, for example, without being limited
15 thereto.

 In addition, although the above described embodiments each have described a mode in which laser light scanning is carried out for a substrate 1 once in a main scanning direction (Y direction), the main
20 scanning direction may be divided into three sections A, B, and C, for example, in FIG. 3. In this way, the size of each scanning region can be arbitrarily set.

 According to the present invention, there can be provided an image data acquisition method capable of
25 minimizing a time between scanning for samples and analyzing scanned image data from the scanning for samples, followed by computing the analysis data.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments
5 shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226